



SOFT-SLING (THAILAND) LIMITED

40/6-7 RAMKUMHAENG RD., HUAMARK, BANGKAPI, BANGKOK 10240

TEL : (662) 3793840, 7316000-2

FAX : (662) 3793889

www.softsling.co.th, email : soft1@softsling.co.th, soft2@softsling.co.th


SHACKLE



G-209



G-2130



SÆNKSMEDEDE STÅLSJÆKLER, GALV.

G-209	G-2130	Dimension mm						
VT art. no.	VT art. no.	SWL	A	D	L	B	C	E
03-400611	-	500 kp	1/4"	8	29	13	20	18
03-400811	-	750 kp	5/16"	10	31	14	21	21
03-401011	-	1.000 kp	3/8"	11	37	17	26	25
03-401111	-	1.500 kp	7/16"	13	43	18	29	27
03-401311	03-401321	2.000 kp	1/2"	16	48	21	33	30
03-401611	03-401621	3.250 kp	5/8"	19	60	27	43	40
03-401911	03-401921	4.750 kp	3/4"	22	71	32	51	48
03-402211	03-402221	6.500 kp	7/8"	25	84	37	58	54
03-402511	03-402521	8.500 kp	1"	29	95	43	68	60
03-402911	03-402921	9.500 kp	1 1/8"	32	108	46	74	67
03-403111	03-403121	12.000 kp	1 1/4"	35	119	52	83	76
03-403511	03-403521	13.500 kp	1 3/8"	38	132	57	89	84
03-403811	03-403821	17.000 kp	1 1/2"	41	146	60	98	92
03-404411	03-404421	25.000 kp	1 3/4"	51	178	73	127	110
03-405111	03-405121	35.000 kp	2"	57	197	83	146	127
03-406411	03-406421	55.000 kp	2 1/2"	70	267	105	184	152
-	03-407521*	85.000 kp	3"	83	330	127	-	165
-	03-408821*	120.000 kp	3 1/2"	95	371	133	-	203
-	03-412021*	150.000 kp	4"	108	368	140	-	229

* Med bøjlehåndtag i stedet for sekskantet boltehead

Sænkmedet kulstof stål

Varmbehandlede, legerede stålbolte

Hver sjækel er mærket med SWL

SWL = arbejdsbelastning

Type G-209 opfylder U.S. Fed. Spec. RR C-271-b type IV klasse 1

Type G-2130 opfylder U.S. Fed. Spec. RR C-271-b type IV klasse 6

Sikkerhedsfaktor min. 5,4 : 1