








# VT ROUND SLINGS

**Version :** Our round slings are manufactured according to DIN 61360, CE Standard and pr EN 1492-2 from polyester yarn. The round slings from 1 to 15 ton are covered with a woven double bag.

The round slings from 20 to 40 ton are delivered with side seam.

The cover is woven from strong polyester material protecting the load bearing yarns of the round slings.

Art.No.	Colour	Dia. mm. Appr.	Working Load	Choked Lift	Open Lift	Open Lift 45°	Open Lift 90°	Open Lift 120°
			 M = 1.0 kg.	 M = 0.8 kg.	 M = 2.0 kg.	 M = 1.8 kg.	 M = 1.4 kg.	 M = 1.0 kg.
86-110100	Violet	16	1,000	800	2,000	1,800	1,400	1,000
86-110200	Green	20	2,000	1,600	4,000	3,600	2,800	2,000
86-110300	Yellow	30	3,000	2,400	6,000	5,400	4,200	3,000
86-110400	Grey	33	4,000	3,200	8,000	7,200	5,600	4,000
86-110500	Red	36	5,000	4,000	10,000	9,000	7,000	5,000
86-110800	Blue	45	8,000	6,400	16,000	14,400	11,200	8,000
86-111000	Orange	50	10,000	8,000	20,000	18,000	14,000	10,000
86-111200	Orange	60	12,000	9,600	24,000	21,600	16,800	12,000
86-111500	Orange	80	15,000	12,000	30,000	27,000	21,000	15,000
86-112000	Orange	100	20,000	16,000	40,000	36,000	28,000	20,000
86-112500	Orange	130	25,000	20,000	50,000	45,000	35,000	25,000
86-113000	Orange	160	30,000	24,000	60,000	54,000	42,000	30,000
86-114000	Orange	200	40,000	32,000	80,000	72,000	56,000	40,000

**Safety factor 8 : 1 / 7 : 1**

**Wide Programme :** The round sling are manufactures to a SWL of 25 tonnes up and a range of circumferences between 2 and 35 mtrs.

For extra protection cuffs can be fitted. Further the round slings can be delivered as simple- or multiparts strap with rings or hooks mounted directly in the round sling.

**Material Specification :** Resistant to acids. Not resistant to alkalies. Oil does not affect polyester. Melting point appr. 260°C. Max. Working temperature appr. 100°C. Elasticity at SWL 2-4 %. The breaking load is unchanged in water.

**All our products will be delivered in accordance with CE machinery directive (89 / 392 / EEC as amended by directives 91 / 368 / EEC and 93 / 68 / EEC.) Certified : DIN 61360 ; EN 1492-1 ; EN 1492-2 ; ISO 9001 ; D.**

**Type Round Strop :** Is a standard round sling enclosed in a cover which has the effect of making the round sling perform as an eye sling.

**Please Specify :** Capacity in ton, working length - meter, protector of sling, **certificate** as required.

บริษัท สลิ่งอ่อน (ประเทศไทย) จำกัด  
SOFT-SLING (THAILAND) LIMITED

40/6-7 Ramkhumhaeng rd., Huamark, Bangkapi, Bangkok, 10240

Tel : (02) 3793840, 7316000-2

Fax : (02) 3793889

www.softslings.co.th email : soft1@softslings.co.th, soft2@softslings.co.th

